

2026 FLORIDA PRO TRUCK CHALLENGE SERIES RULES

PLEASE BE SURE YOU HAVE READ AND UNDERSTAND THE GENERAL RULES, SAFETY RULES AND DRIVER SAFETY EQUIPMENT BEFORE CONTINUING.

The word STOCK used within this set of rules means as originally produced by the manufacturer for that make/model/year of car with no altering or modifications. Stock replacement parts ok but must be same dimensions, weight, and/or volume as OEM the part. Determination of whether an aftermarket part is legal will be the tech inspector's decision.

- No carbon fiber, tungsten or titanium permitted anywhere on truck.
- No traction control device(s) of any kind.
- PAC 1210x Valve Springs allowed.

WEIGHT:

1. 602 with Factory or Series Seals 2850 lb. with 57% left side.
2. 603, M6007S347 JR and any unsealed Crate motors 2950 lb. with 57% left side. Fake/ aftermarket seals 3000lb. ••• These weights can be adjusted at the tracks discretion to equalize the competition, with verbal then written notice •••

2

ENGINES: Vacuum Rules (Each truck must have a vacuum port and fitting to check)

- 1 603 Crate -18 Minimum @ 950 rpm
- 2 2. 602 Crate -18 Minimum@ 950 rpm
- 3 3. 347 Jr Ford-19 Minimum@ 950 rpm

CRATE ENGINES: GM 602 with Holley 650 HP 4150-80541 allowed but totally by the GM manual with a Maximum 9.6:1 compression. GM 603 with Holley 500 CFM old style 4412 only but must follow the Gm Manual unless listed below.

603 OPTIONS ONLY:

1. Optional valve springs stock diameter, no double springs max 130 lbs. Comp# 941 is allowed.

Self-aligning Stamp Rollers or 1.5 Roller rockers only.

Maximum 10.3:1 COMPRESSION RATIO.

4. MAX overbore .030 + .010.

FORD 347JR:

This engine must follow the Ford Racing Technical Manual only. Maximum of 10.2: 1 compression ratio.

FORD 351 W:

May use m6513-bh bearings.

2. Intake to be used must be intake that came with motor only.

3. 52cc minimum on heads

4. Must maintain 10.2:1 compression ratio

5. Due to several cam combo's these are the numbers that are legal. M6250-e303, m6250x303 and m6250-z3003.

6. Minimum deck height .014

7. Refer to Ford Performance Manual for any other details.

Max overbore .030 + .010 for wear. Note: All engines must have an inspection plug w/plug (minimum 1 ") on left front of oil pan.

Carburetor / Air cleaner:

1 Carburetor- Unaltered Holley old style 4412, 500 CFM gauge legal with a maximum 1.065 spacer/adaptor between intake and carburetor and choke horn may be removed.

2 2. 602 Crate can run a Holley 650 HP 4150-80541 gauge legal four barrel. No alterations or modifications, with a maximum 1.065 spacer/seal between intake and carburetor.

3 3. A round un-altered air cleaner element with a maximum diameter of fourteen (14) inches with a maximum height of four (4) inches is required. All air must be filtered thru this filter or through the use of a Cold air box on the top of the carburetor that encases the air filter. No ram air will be allowed.

Updated: Tuesday, March 17, 2026

4 4. Hoods to remain stock with the following opening of 2.5" x 20" cut in the rear of the hood and centered behind air filter and a 1.5" x 1.5" X 20" heat deflector may be installed on the fire wall at this opening.

5

Fuel system:

- 1 Sunoco 110 or equivalent, no fuel additives, ethanol or E85 will be permitted. Track Officials reserves the right to test the fuel at any time. Fuel pump--stock mounted mechanical pump only.
- 2 The fuel cell must be a magnetic steel container made from no less than 22-gauge magnetic steel.
- 3 The use of ice, wet or dry, for the purpose of cooling the engine, air cleaner, or fuel system is not allowed.
- 4 Maximum fuel cell capacity is 22 gallons and must maintain a minimum ground clearance of 8-inches.
- 5 OBERG Fuel Valve # SV-0828 or SRI # FFF-FSV Mandatory near cell and after filter.

Cooling system:

- 1 Stock type water pump, no electric with Recommended to have overflow hose mounted to right corner of windshield.
- 2 Water wetter ok, no anti-freeze may be used.
- 3

Exhaust:

- 1 Steel headers optional with a maximum diameter of 3" collectors and 3" exhaust pipes the rest of the way out.
- 2 All exhaust system must exit past the driver's compartment. The minimum exhaust system ground clearance is 3 inches.
- 3

Engine location:

- 1 Must be centered between frame rails, 1" tolerance.

- 2 Crankshaft height is 12" from center of the crank to the ground. Engine placement is measured from the spark plug (closest to the radiator) centerline to an imaginary line projected between the left and right upper a-arm ball joint as follows; 3 A. All Chevrolets: 4 inches on the driver's side forward of the ball joint.
- 4 B. Fords 1. 75 inches on passenger side forward of ball joint.

Ignition:

- 1 Mandatory Crane Cams, FAST Ignition part# 6000-6701 or JMS - Daytona Sensors' part# 6000-6701 K only as produced. Mounted on right side of truck dials pointed out the passenger side on original plate. The mag positive & negative shall be a maximum length of 62 inches. Must remain uncut or spliced and on top of dash in clear view.
- 2 Only one box will be permitted must be mounted on right side.
- 3 All wires must be exposed and in plain view and easily traced by tech officials.
- 4 Maximum RPM's will be Crates 6300 and Built 7000.
- 5 Single Battery 12-volt system only and battery disconnect switch is mandatory and accessible to the safety crew and driver.
- 6

Transmission:

- 1 Only GM Turbo 350 and Ford C4 or C6 automatic transmissions allowed with following exceptions. No drilling or lightening on the transmission or interior parts except the following items for oiling purposes. Front Planetary Reactori Gear per spec - see tech for spec sheet. Sun shell cover (must be a solid stock type) may be drilled at back per spec -see tech for spec sheet.
- 2 Must have all forward and reverse gears working. No modifications.
- 3 GM Turbo 350 may use 2.75 low gear-1.57 second gearoption and with no turbo 200/250 parts used in 350 transmissions.
- 4 No aluminum or billet parts allowed in transmission.

- 5 Torque convertor must be minimum diameter of 1 O" and working.
- 6 Transmission coolers with fans allowed and all cooling lines must be steel braided with screw on fittings.
- 7 Safety Bell Housing and/or flex plate shield ok.
- 8 Solid output shafts only, no gun drilled or hollowed shafts allowed.
- 9 JW Transmissions, TCI Transmissions or others allowed as long as they meet these rules.
- 10 Standard steel or aluminum 3-speed or 4-speed OEM or OEM style synchronized manual transmissions must have helical gears only. No straightcut gears, magnesium or gun-drilled main shafts permitted. Two lever shifter or Hpattern shifter only. No Rankin type or cluster-disconnect transmissions or 2-speed transmission will be permitted.
- 11 No internal clutch-type transmissions allowed and must have external clutch, pressure plate, and flywheel assembly.
- 12 Transmission must have all forward gears and one (1) working reverse gear.
- 13 No overdrive or under driven transmissions permitted. High gear must be 1 to 1 and no other gear may have a ratio higher than 1.20 to 1.

Clutch/ Flywheel/ Drive shaft:

- 1 Standard OEM or OEM-type and size clutch, steel pressure plate, steel flywheel, and throw-out bearing permitted.
- 2 No Light Weight Parts: 10,000 RPM etc. Stock Clutch minimum 1 O" Solid hub clutch only and must have pad or full circle.
- 3 Clutches must be positive engagement design. Slider or slipper clutch designs are not permitted. No carbon fiber clutches.
- 4 Fly wheel must weigh minimum of 14 pounds.
- 5 Standard transmission must use shatter proof bell housing with 2" hole in bell housing for inspection.
- 6 Only Steel driveshaft and must be painted white with truck number on it with 2 drive-shaft safety loops mandatory

Truck:

- 1 Only GM Metric frame 1978-1987 may be used with a 6" minimum ride height on chassis. Frame can be X" d.
- 2 OEM GM metric frame only may be used 1978-1987 Chevrolet Malibu, Monte Carlo or Unaltered replacement Johnson Chassis #JCI-09-1B ("XYZ" or Johnson clip and/or chassis must be raced as manufactured by Johnson Chassis, any modifications will be deemed illegal per their Watchdog Inspection Tools. Frames must retain original 108-inch wheelbase. Maximum allowable difference from side to side is 1/2 inch.
- 3 Maximum Tread Width 63" front and rear (62" using Referee).
- 4 Chassis must remain stock unless otherwise specifically noted in rules.
- 5 Frame may be fabricated from 6" forward of the centerline of the rear axle and from front sway bar forward.
- 6 Cross member must remain stock and in stock location, it may be notched for oil pan clearance only and must be boxed with 1/8-inch steel. If yours had been cut you must add square tube metal to make it same height, width and depth as a stock one.
- 7 All pick up points must remain stock in stock locations.
- 8

Front Suspension / Steering:

- 1 Front suspension components must remain stock in stock location, unless otherwise noted in another rule.
- 2 All pick up points must remain stock in stock locations. Front lower control arms may not have any modifications (holes, lightening).
- 3 Heavy-duty steel or aluminum aftermarket hubs & rotors are required on the right front wheel.
- 4 Springs must mount in stock location. Top of frame may be changed to add wedge bolts or to allow for spring removal.
- 5 Shocks must be mounted directly to the lower A-arm.
- 6 Pitman arm and steering arm may be changed but remain stock length for make and model. Aftermarket center link is permitted.
- 7 Stock inner tie rod with steel heim-type tie rod ends on the outers will be permitted.

- 8 Upper and Lower ball joints may be any bolt on or screw in type ball joints. No relocating of lower ball joints allowed.
- 9 A maximum of one 360-degree spring rubber allowed on front or rear springs. Coil spring rubber inserts are permitted, no leaf springs or torsion bars permitted.
- 10 Steel, poly or mono-ball bushings ok, no offset or eccentric bushings.
- 11 Sway bar must be 1-piece stock 1 3/8" maximum diameter.
- 12 Stock OEM steering box, may change ratio (updated 5-21-19) in stock location.
- 13 Spindles or Part #91034501 3-Piece IMCA 1979-Up GM Metric Mid-size Spindle, bearings and hubs, Stock HD aftermarket hubs and rotors are allowed. Spindle savers are recommended. Steering arms must be same length on right and left.

Rear Suspension / Rear-end:

- 1 Rear differential housing must be stock steel 7.5" -10 bolt GM or 9" Ford housing. All rear-end parts must be steel and a 1" inspection hole in cover is recommended.
- 2 OEM stock rear trailing arms only and must mount in original holes in frame. No cambered rear ends permitted. Distance between the centers of the bolts on the upper arms should be no less than 10 V4 ". The upper trailing arms may be redrilled on rear-end side only to adjust pinion angle and washer welded back. Must use stock OEM factory control arms; bushings at both the front and rear of the trailing arms must be original rubber or polyurethane.
- 3 Rear spring perch must remain on the top of the axle tube. Rear springs must mount on top of axle tube and must be standard 5" diameter rear springs. Shocks mount in stock location and must be the same distance in from rotors on each side.
- 4 Ring gear and pinion must be stock and mount directly in housing.
- 5 Only stock ring and pinion, off the shelf available gears allowed. No custom ground or lightened gears allowed. GM 273-456 gears, Ford 9inch may use 300 and above gears, non-lightened, non-back cut, non-polished gears. Welded spider gears, mini spool or any spool must weigh 6.1 pounds or more with stock steel/cast carrier will only be allowed.
6.
Axles must maintain a minimum diameter of 1.200" with a tolerance of -.010. Purchase price not to exceed the advertised pricing of \$220 and must be available for any competitor to purchase at that price. No titanium or "wrap-up" axles allowed.

- 7 No rear Pan-head or sway bars.
- 8 Rear spoiler must be centered.

SHOCKS :

- 1 Only 1 steel body non-adjustable shock per wheel permitted. Adjustable shafts, base valves and canisters are not permitted.
- 2 Shocks may have Schrader Valves and internal parts must remain as purchased with a Maximum cost of \$250.00 per shock.
- 3 Internal rebuild parts must remain as purchased in that shock not to exceed the retail value. Shocks can be claimed for \$200.00 each by track or competitor. Refusal will be a DQ, loss of money, points and a \$200.00 fine.
- 4 No bump stops, coil binding, bump springs or chassis limiters (up or down).

Body:

- 1 (See Diagram) Approved Truck body Manufacturers are: AR Bodies, Lightning Light and Five-Star. May make own aluminum body pieces, NO carbon fiber and must be approved by Track, and fit templates.
- 2 Only approved bodies are: 1997 -2009 Chevy C-10/C1500 Silverado, 1997 -2009 Ford F150, 1997 -2009 Dodge Ram, 2004-2009 Toyota.
- 3 Body must be centered of the frame with wheels in center of wheel wells with 2" tolerance. All body parts must be attached firmly to cage or frame and is subject to approval. Body ground clearance is a minimum of 4 inches measured anywhere.
- 4 All body support brackets must be solid and located inside the body structure.
- 5 Nose Width is 81" maximum. Front air dams must maintain their original configuration with a maximum of (4) four splitter supports.
- 6 Maximum rake for roof is 1". Front windshield braces are mandatory. Windshield angle must be 35 degrees+ or -1 degree.
- 7 Minimum side window opening must be at least 16" and may have 1/8" Lexan vents only, 9" high, 12" length max
- 8 Front and Rear windows must be full 1/8" Lexan.

- 9 Hoods to remain stock with the following opening of 2.5" x 20" cut in the rear of the hood and centered behind air filter and a 1.5" x 1.5" X 20" heat deflector may be installed on the fire wall at this opening.
- 10 Fiberglass, sheet metal or aluminum rear deck lids flush with quarter panels are mandatory must be able to open for technical inspections.
- 11 No Lexan or metal air deflectors on rear deck or attached to rear down bars complete.
- 12 6" x 60" clear solid rear spoiler is mandatory with a 55 Degree Minimum angle with approved braces on back side.
- 13 Unmodified Stock rear bumper cover is mandatory and must be complete.
- 14 Rear deck height maximum is 40 inches.
- 15 No tape allowed on truck unless approved for damage.
- 16 Bottom of rear quarter panels must follow body line of rear bumper cover.

Interior:

- 1 Vehicle interior must be complete and shield driver from the ground, engine compartment and fuel cell area.
- 2 Driver's floor must be steel; the rest of the compartment can be from steel or aluminum but must be fully enclosed and extend from left to right side of truck.
- 3 Truck must have a rear firewall to separate driver from fuel tank. Firewall may be welded, riveted or bolted.
- 4 May have installed digital dash panels.

Brakes:

- 1 Four-wheel disc brakes must be in full working condition with any OEM appearing single piston caliper only.
- 2 Only cast iron or steel rotors allowed.
- 3 **Absolutely NO Fans or Colling devices allowed for breaks**

Tires and Wheels:

- 1 Track approved tires only. FOR NSS ONLY Tires will be checked by durometer. Tires must punch 50 or above. Can be checked at anytime.

2 8" steel racing wheels with any offset and no wheel weights or bleeders allowed. Any safety hub with 5/8" wheel studs only.

3

Driver Safety Rules:

1 You must have proper rated 2018 or newer Snell approved helmet 2

A type of head and neck restraint is mandatory.

3 Complete SFI or FIA RATED fire-suit, gloves, and shoes are mandatory in good condition.

4 Driver's window net SFI or FIA RATED must have quick release, with latch at top left and be no older than 5 years-old.

5 Commercially made aluminum racing seats with rubber pads mandatory.

6 Safety SFI or FIA RATED Harness 5-point minimum must be no older than 5 years old.

7 Proper resilient padding for roll bar use must be installed on roll cage around driver. Steering Wheel must be padded.

8 Fully Charged fire extinguisher mandatory and On-Board fire system is highly recommended.